


**HAND
BOOK**

British Home



MICROCOMPUTER

NASCOM 1

SOFTWARE NOTES

NASCO
SALES LTD



Electronics
(LONDON) LTD.

92 BROAD STREET
CHESHAM, BUCKS.

Tel: Chesham (02405) 75151
Telex: 837571

THE OPERATING SYSTEM FOR NASCOM 1

-----NASBUG-----

1.

The personality of any computer system is governed by its operating system. For the Z-80 based NASCOM 1 the Operating System is called Nasbug and has been designed to assist the user to write and De-bug programmes written into the computer's memory in OBJECT CODE. The fundamental base of all Nasbug's operations is HEXADECIMAL. All DATA or CODE is entered in this form and this description assumes that all variables are in HEX.

NASBUG commences action immediately the CPU RESET KEY is pressed. Its initialisation can be read in the listing which should be read in conjunction with this description. The apparent functions to the user are that the screen is cleared and the PROMPT CHARACTER appears in the first location of the lowest line of the SCREEN. The appearance of the PROMPT means that NASBUG is waiting for your command. It also means that the hardware is fully operational and that the REFLEXIVE DATA has been loaded into RAM (See section 11). After the PROMPT the user may enter any of the following NASBUG COMMANDS:

L	Load from Serial Interface
Baaaa	Set Breakpoint
Maaaa	Modify/Inspect Memory
Taaaa bbbb	Tabulate Memory
Daaaa bbbb	Dump Memory to Serial Interface
Caaaa bbbb dddd	Copy Memory from a block starting at (a) to a block starting at (b) The length of each block is (d).
Eaaaa	Commence Execution at a (a can be implied).
Saaaa	Single Step Execution at a (a can be implied).

NOTE that there should be no space between the COMMAND and the first ADDRESS. All COMMANDS can be EDITED.

/ 1. (cont'd)

NOTE that the lower case letters above are the ARGUMENTS of the COMMAND and are always ADDRESSES. The COMMAND is taken from the screen and can be EDITED by use of the BACK-SPACE KEY. (No action is taken until the NEW LINE KEY is pressed - this applies to ALL commands).

NOTE that LEADING ADDRESSES ZEROS are NOT required. Leading DATA zeros are NOT required. In all following sections, the characters written by the USER are UNDERLINED.

2.

Maaaa

To either examine or change the contents of READ-WRITE MEMORY, the M command is used followed immediately by an address.

The user can then enter a series of data bytes which will be written into successive locations. The data must not flow into the next line i.e. before it does so a NEW LINE must be entered. Each data byte must be separated from the next by a space.

Characters entered by the USER are underlined.

The letters NL serve to represent the pressing of the NEWLINE KEY by the USER. The following example shows a programme being entered by the user. The places at which the user has pressed NEWLINE are entirely by personal preference, as long as the data string does not ever flow into the next line since NASBUG uses only those characters which appear to the right of the PROMPT on the bottom line of the screen.

```
>MCFA NL  
0CFA 00>3A 00 0E NL  
0CFD 00>3C  
0CFE 00>32 00 0E NL  
0D01 00>CD 3B 01 CD 35 00 NL  
0D07 00>C3 FA 0C NL  
0E0A 00>. NL  
>
```

The M command will continue until aborted by use of the . (full stop) key plus NL.

3.

Taaaa bbbb

The Tabulate Command is to display a block of locations onto the screen. There is little point in calling for a block longer than 68H. (NOTE this represents 68 as a HEXADECIMAL VALUE and can either be 68H OR sometimes H'68'. The DECIMAL equivalent is $6 \times 16 + 8 = 104D = D'104' = H'68' = 68H = 16'68'$. If a longer block is called for it will overwrite the screen and only the last H'68' locations will be visible at the end.

>TCFA D0A NL
0CFA 3A 00 0E 3C 32 00 0E CD
0D02 3B 01 CE 35 00 C3 FA 0C
.
>

4.

Daaaa bbbb

THE DUMP COMMAND uses the same code in the operating system as TABULATE thus its data format is identical. What is not apparent in the T command is that each line of text on the screen is not as it was originally written. The line is initially generated as below which is the format for recording on to cassette or TTY. The D command causes the same format line as for T to be transmitted not to the screen but to the TTY (or SERIAL OUT) only and precedes the start of transmission with the operation of the 'START PERIPHERAL DRIVE' Light Emitting Diode (LED) which the user should take as their cue to start the cassette motor running. In practice the motor can be operated a while before since no false characters are transmitted ahead of the main data. The end of the block is identical to that for T except that the System turns the LED off just prior to presenting the PROMPT for the next command.

The format below is broken after the user's NEW LINE to show the cassette characters which do not appear on the screen. The duration of the DUMP command is a function of the UART CLOCK and is about 25 characters/second for cassette.

>DCFA D0A NL
>

```
0CFA 3A 00 0E 3C 32 00 0E CD 97 85 85 NL
0D02 3B 01 CD 35 00 C3 FA 0C 16 85 85 NL
.
```

5.

Caaaa bbbb dddd

The COPY COMMAND copies the contents of a block of memory starting at location a and continuing until location a + d into the block starting at b, thus the last byte to be copied will be from a + d to b + d.

NOTE that the COPY COMMAND MUST BE USED WITH GREAT CARE. Since the data is transferred immediately, data in the overlapping regions of blocks which overlap is destroyed. Thus to copy successfully the user must observe:-

b must be greater than a + d

DOWN COPYING can be effected by using an intermediate data area to transfer the data to in order to copy down. As long as this block is clear of a + d the command can be used again to transfer back to the overlap region. This procedure is demonstrated in the following example to 'open up' a block of code to insert a byte. The user has omitted to put in a byte at address H'D05 and the last address of the data is at H'D37'. The COPY command is therefore used to transfer the block H'D05' to H'D37' inclusive to an unused area at H'F00'. This block is then transferred back to a block starting at H'D06'. The C command can be used to set whole areas of memory to any code by executing the copy command with the address of the first block being one address less than the address of the second. The third argument is the number of bytes to be set to the value of the contents of the first byte.

```
>TE00 E0F NL  
0E00 01 02 03 04 05 06 07 08  
0E08 09 0A 0B 0C 0D 0E 0F 10  
>
```

```
>CE05 F00 32 NL  
>CF00 E06 32 NL  
>
```

```
>TE00 E0F NL  
0E00 01 02 03 04 05 06 06 07  
0E08 08 09 0A 0B 0C 0D 0E 0F  
>
```

6.

E aaaa

The EXECUTE COMMAND transfers the contents of the REGISTER SAVE AREA into the internal registers of the Z-80 and finally forces PC to aaaa. EXCEPT that after encountering a BREAKPOINT (see section 8) 'a' need not be specified since, if it is not, the last executed value for PC will be put into PC by the F Command. This also applies to the S COMMAND (see Section 7).

```
>ME00 NL
0E00 00>20 NL
0E01 00>.NL
>ECFA NL
!"#$%&'()*+,- (Etc)
```

NOTE that the first instruction initiates the SINGLE STEP procedure which is then ignored and execution continues normally. Thus, the first instruction to be executed will receive a NON-MASKABLE INTERRUPT during its execution. All subsequent instructions will not. This means that the HALT instruction will not be obeyed if it is at the address of the current E command where specified or implied.

This shows the Z-80 executing the HALT (at H'0F03') but being interrupted out of it by the NMI trap laid for it by NASBUG. The next sequence shows the Z-80 halted and this state is indicated by the HALT LED on the NASCOM I card.

```
>MF00 NL
0F00 00>0 0 0 76 0 C3 86 2 NL
0F03 00>.NL
>EF03 NL
> (BACK IN MONITOR LOOP)
>EF02 NL
- (HALTED).
```


7.

S aaaa

As with the EXECUTE command the 'a' may be implied, BUT SO MAY 'S'. This command is one of the most useful commands available for checking correct program execution. It is so useful that the NEW LINE KEY has been programmed to extend its function into not only permitting the SINGLE STEP ADDRESS to be implied (as being simply the next instruction), but the S CHARACTER ITSELF is implied, thus the executions of the SINGLE STEP COMMAND can be continued, once initiated by means of only the NEW LINE character. Thus since the operation of the SINGLE-STEP proceeds by means of the NMI input (i.e. single-stepping is partially hardware driven) the S command can be used to examine ROM code i.e. NASBUG will step through ROM code.

The use of the implied address of both E and S is illustrated in the following example:-

```
>B0 NL
>E0 NL
>BD04 NL
>E0 NL
>SCFA NL
1000 0CFD 2042 FFCF FF00 0600
>S NL
1000 0CFE 2120 FFCF FF00 0600
>     NL
1000 0D01 2120 FFCF FF00 0600
>ME00 NL
0E00 21>     NL
>S NL
0FFE 013B 2120 FFCF FF00 0600
>E NL
!1000 0D04 2120 FFCF FF00 0600
>E NL
"1000 0D04 2220 FFCF FF00 0600
>E NL
#1000 0D04 2320 FFCF FF00 0600
>B0 NL
>E NL
$%&'()*+,-
```

(ETC)

S (cont'd)

At every execution of SINGLE STEP, the following registers internal to the Z-80 are put up onto the SCREEN:-

SP	PC	AF	HL	DE	BC
Stack Pointer	Program Counter	Accumulator and Flags	Register Pair HL	Register Pair DE	Register Pair BC

8.

B aaaa

The BREAKPOINT COMMAND should be entered at location 0 whenever NASCOM I is first switched on since the BREAKPOINT ADDRESS is saved in memory. The RESET button does not clear this location otherwise the place would be lost if the RESET was used to return to NASBUG. Since the processor has no other means than RESET to know if it is first powered up or not, this setting of a breakpoint at 0 should become a user habit on first turning on the machine.

The use of the BREAKPOINT is illustrated in Section 7. The purpose of the BREAKPOINT is to insert a trap sequence into the code in RAM at the address specified after the B. This puts H'E7' into aaaa and removes the byte which existed there into address 0C17. The program is then executed until it finds the BREAKPOINT and then execution is transferred to NASBUG at location 0020. This causes the current registers to be put up onto the screen in the same way as for SINGLE STEP. The original code is restored by entering BO i.e. by setting a new breakpoint at location 0.

After setting a breakpoint the next instruction MUST be an Execute instruction - always follow "B" with "E". (See previous Example.)

9. L

The LOAD command executes a routine which interprets data on the last line of the SCREEN as data in the format of the DUMP command but to be loaded into the memory at the address specified at the beginning of the line. The process is the exact reverse of the DUMP (or TABULATE) code but with the following exception: If the check-sum byte is not true, the line is not loaded into the memory but is SCROLLED on to the next line on the SCREEN. Thus at the end of the LOAD (which occurs when the end-of-DUMP characters are recognised) the SCREEN contains only invalid lines which have not been loaded due to tape or recorder errors. By re-winding the tape, the errors can usually be corrected by re-loading. If a note is taken of faulty lines and the recurrence of the same line is observed only then will it be necessary either to load again or to correct the line using the M command.

10.

Software implications of NASBUG.

The single step feature occupies the NMI line the processor so that this input and the associated instructions are not available to the user, without modifying the hardware. NASBUG has been written to be maximally usable by the user. All commands are in the form of sub-routines which can be called by the user software.

The COMMAND TABLE is arrived at reflexively so that its table of commands can be extended i.e. users can write their own commands and use them in conjunction with NASBUG.

The KEYBOARD TABLE is called reflexively so that it can be re-written in RAM to re-assign values to each key, or to increase the number of keys used.

(NOTE the LICON KBD uses a special circuit for key operation and so additional keys need additional hardware to access them).

11.

Sub-routines in NASBUG which can be called by the user are:-

KDEL	at	0035	Gives a 6ms delay
MOTFLP		0051	Turns cassette motor lamp/drive on/off (alternate calls)
SRLOUT		005D	Puts A into UART
KBD		0069	Returns with Carry SET if a character was found from the Keyboard. Character in A.

Using reflections:-

\$KTAB This address in RAM has the address of the new keytable.

(NOTE that both CRT and KBD are entered by NASBUG via a JUMP in RAM. This means that the user can alter the locations at \$CRT and \$KBD to cause NASBUG to look elsewhere (in user RAM) for both these subroutines).

CRT	013B	A character in A is put onto the SCREEN or CURSOR moved (BS or CR) or SCREEN is CLEARED (FF).
-----	------	---

There is a reflexive jump at \$CTAB which gives NASBUG the start address of its own COMMAND TABLE. This means that the user can add COMMANDS by changing this jump. The existing commands can all be incorporated into this table.

CHIN	003E	This routine calls \$KBD and also looks at the UART to see if any SERIAL DATA is available. If either occurs, the routine returns with Carry set and the character in A.
------	------	---

\$NMI is the address which the NMI uses reflexively. It can be changed.

12.

The example program illustrated in Section 7 shows the use of some of the sub-routines available in NASBUG. A listing of the program would be (in SOURCE STATEMENTS):

```

                                ORG  H'OCFA'      Start code at CFAH
CRT                             EQU  H'013B'
KDEL                            EQU  H'0035'
REG                             EQU  H'0E00'
LOOP                            LD   A,REG
                                INC  A
                                LD   REG,A
                                CALL CRT          Go to the subroutine at 13BH
                                CALL KDEL        Go to the subroutine at 35H
                                JP   LOOP        Return to the first instruction
```

Only the statements from LOOP onwards are actually coded, the code being as entered in the example of section 2.

13.

The memory locations available for user programming in the unexpanded Nascom 1 extend from 0C50 to approximately 0FE0 (depending on the use made of the user's stack).

14: DETAILS OF MEMORY USED BY NASBUG

	0 8	1 9	2 A	3 B	4 C	5 D	6 E	7 F
0C00	RAMZ Port 0 ← KMAP — Old keyboard switch contents —————							
0C08	→	ARGS Command Char.	No. of Args.	ARG 1		ARG 2		
0C10	ARG 3		NUM Used by NEXNUM Subroutine		RAME BRKADR Breakpoint address		BRKVAL User Code	
0C18	CURSOR Cursor Address		Curflg	← Bottom of Monitor Stack - - - - -				
0C20	- - - - -							
0C28	- - - - -							
0C30	- - - - - Top of Monitor Stack →		STACK C (R.BC) B		E (R.DE) D		R. HL L	
0C38	H	R.AF F A	R.PC PC.1 PCh	R.SP } Initr } SP.1 SP.h		\$KTABL ←		
0C40	Keyboard Table Length	\$KTAB0 Keyboard table origin	\$KTAB Keyboard table start	\$CTAB Command table start		\$NMI C3H (Jump')		
0C48	NMI 1 h	\$CRT C3H (Jump')	CRT 1 h	\$KBD C3H (Jump')		KBD 1 h		


MEMORY USED BY NASBUG

(TO GENERATE THE CORRESPONDING MAP ON-SCREEN TYPE:-

TC00 C4F NL .)

(THE FIRST LOCATION AVAILABLE FOR USER PROGRAMMING IS 0C50.)

If argument supplied, put in R.PC
Restore BC, DE, AF (First AF is old HL)
Restore user SP
Push user PC on stack
Restore HL
Save AF while activating NMI
RETN to user's instruction



305 TRAP:

Add 1 to users PC on stack
(Decrement later in code common
to TRAP & Breakpoint)
Save AF, HL;
Clear NMI flag in port 0
If CONFLG nonzero (i.e. was an 'E')
Save users instruction at breakpoint,
Insert RST 4 there.
Restore HL, AF, decrement PC,
RETN to user's code.
Otherwise
Save DE and go to
BPTI (326)

Breakpoint entry 020:

Save AF, HL, DE
then:

326 BPTI:

Save BC; HL ← SP;
Copy registers from User stack
to register save area in Monitor's RAM

Decrement user's PC so it points to
Breakpoint address.
print out users registers

347 REGSI:
359 STRTU: restore instruction at breakpoint
and go to
PARSE

069 KBD:
(via \$KBD) Save regs.
Clear counter
Initialise pointer to map
Read Row 0 (shift)
into KMAP

KSC1: Increment counter.
Increment KMAP pointer, check for change.
If different → KSC2

KSC1A: Repeat 8 times

KSC 8: Clear carry (no key found)

KSC 9: Restore regs - return

KSC 2: delay. (KDEL - 035)
read again.
Calculate column no. of changed bit, (C)
bit mask (D).
Check whether change really occurred
if not go to KSC 1A
Update map
If a release go to KSC 1A
Manufacture magic number from
shift key, loop counter, bit number
Search KTAB for this number. (via \$KTAB)

(If not found, clear shift bit & try again)

If still not found go to KSC8

Calculate ASCII code from address within

KTAB (OEA)

OED KSC3: set carry (character found), return.

O3E CHIN: check keyboard & UART until
character received.

O5D SRLOUT: put character in UART
wait until sent.

O53 FLIP: flip a bit in Port 0

O4A FLPFLP flip & flop a bit in Port 0

O35 KDEL: delay; PUSH & POPs lengthen the loop

13B CRT: ignore character 0.
Save regs.
FF? yes. put -1 in top left,
then 48 spaces
then 16 zeros } repeated 15 times
then 48 spaces }
then -1 in bottom right

CRT0: set HL to bottom left

CRT1: put cursor on screen, save cursor

CRT2: restore regs, return

Replace cursor with blank.

BS? → decrement cursor, skip
over margins.

If -1 reached, increment cursor
again; go to CRT1 to put

cursor on screen & return.

CR? → CRT3 (scroll)

Ordinary character : Put it on screen.

Skip cursor over margins

-1 reached? no → return via CRT1

195 CRT3: Scroll; clear bottom line and go to
CRT0 to reset cursor.

1DB INLINE: print prompt

1DE INLO: get character; BS? → INL2;
CR? → return via CRLF

1E9 INL1: display character; → INLO

1EE INL2: BS?

Check for prompt, if so go to INLO

otherwise go to INL1 to do backspace.

(RST 5)

028 PRS: Pick up 'return address'.
Send characters until 0 to CRT
Return to instruction after 0.

224 B2HEX: save number, shift top hex to bottom.
Call B2HEX1 (to print it)
restore number

24D B2HEX1: print bottom hex digit, return.

25A NEXNUM DE points to line on screen.
Skip blanks
NUM = number of digits in number.
NUM+1, NUM+2 ← number.

1AD MODIFY Pick up address from ARG1

1B0 MODI: Print address,
Print contents.

Call inline to read line.

1BF MOD2: Number there? → modify memory,
 increment address, → MOD2

ICF MOD3: '.' ? go to return.
Any numbers on line? no, → increment address then
go to MOD1

IFC TABCDE: address = (ARG1)
TBCD 1: address = ARG2?
 Yes → print '.'; return.
Clear checksum.
Print address (TBCD3)
216 TBCD1A: Print memory (TBCD2, accumulates checksum)
Increment address
Repeat 8 times from 1A:
Print checksum.
Backspace over checksum then go to
TBCD 1 :
22B TBCD2: Accumulate checksum, print in hex.
232 TBCD3: Print address using TBCD2.

3D1 DUMP: Turn on Motor then call
Delay.
Set \$CRT to SRLOUT
Call TABCDE
Restore \$CRT to CRT
Return via routine to turn motor off.

37C LOAD: turn on motor

LOD 1: set to beginning of line

LOD 1B: get character, ignore BS

Not CR? go to display, then back to LOD1B

LOD 1A: Pointer to beginning of line

'.' ? to MOTFLP to turn off & return

Read numbers into top left screen margin.

Check checksum. If incorrect, scroll, then go to LOD1

then copy into memory → and return to LOD1.

3EF COPY Block transfer from the block starting ARG1 to the block starting ARG2 the number of bytes in ARG3.

SECTION B: NOTES ON MONITOR LISTING

HEXASM V005 ASSEMBLY ON 15-FEB-78 AT 21:58. PAGE 1 ,LP:<CSDOC
DK:CSDOC.SRC HEXASM NOTES

HEXASM NOTES
=====

Numbers are normally in decimals.
Numbers in other bases are specified by:
base,number e.g. 16'FF = 2'11111111 = 255

'*' is the 'bit' operator, eg *7 = 16'80, *0 = 1

'A gives the ASCII code for A, i.e. 65

Angle brackets < > are used as brackets within expressions
the statement FRED=3; equates the symbol 'FRED' with 3

'.' is the location counter, e.g.
.S sets the location counter to 3 (ORG 3)

RAM. specifies the start of RAM
.ROM; .RAM; switch between ROM and RAM

':' is used to separate statements

.WORD 1,2,3; [assembles 3 words containing 1, 2 & 3]
.ADDR -1,1; [assembles as 2 double-words (low order first)
.BLKW 3; [reserves 3 words as RAM
.BLKA 2; [reserves 2 double words

A~B; [is equivalent to LD A,B
A~#3; [is equivalent to LD A,3
A~FRED; [is equivalent to LD A,(FRED)

load's which have no direct Z-80 equivalent are treated as two instructions;
the first loads the accumulator, the second stores the value. e.g.

0014 3E053207003E0532 FRED~#5; [=] A~#5; FRED~A;

other shorthand's are:

001E B7B7 TSTA; [=] OR A;
0020 AF4F CLA; [=] XOR A;

the following opcodes have different names in the Z-80 manual:

CMA; = CPL
DBNZ LABEL; = DJNZ LABEL;
J LABEL; = JP LABEL;
BR LABEL; = JR LABEL;

operations which normally take one argument can be given more than one, with the expected result. e.g.:

```
0022 F3C5D0F5C5D5 PUSH AF,BC,DE; [=] PUSH AF; PUSH BC; PUSH DE;
```

the code:

```
0028 20033A0700 IF Z; A~FRED; FI;
```

is equivalent to:

```
002D 20033A0700 BR NZ lab1; A~FRED;  
0032 lab1;
```

the code:

```
0032 2005 IF Z;  
0034 3A0700 A~FRED;  
0037 1B03 ELSE;  
0039 3A0600 A~JIM;  
003C FI;
```

is equivalent to

```
003C 2005 BR NZ lab2;  
003E 3A0700 A~FRED;  
0041 1B03 BR lab3;  
0043 3A0600 A~JIM;  
0046 lab2;  
lab3;
```

in IF FRED Z; the code A~FRED; TSTA; is inserted before the first branch.

HEXASM V005 ASSEMBLY ON 15-FEB-78 AT 21:33. PAGE 3 ,LP:<CSDOC
DK:CSDOC.SRC HEXASM NOTES

JIM=6
FRED=7
.END

0046

HEXASM V005 ASSEMBLY ON 15-FEB-78 AT 21:33. PAGE 4 ,LP:<CSDOC
SYMBOL TABLE

FRED =0007
JIM =0006
LAB1 :0032
LAB2 :0043
LAB3 :0046
RANTOP:0000
RAM. =0000
RONTOP:0046
ROM. =0000
 =0046

SECTION C: NASBUG MONITOR LISTING

HEXASM V003 ASSEMBLY ON 12-APR-78 AT 17:02. PAGE 1 ,LP<CSMON
DK:CSMON.SRC Z-80 Monitor

RAM = 16'000

initialise stack pointer and RAM

```

0000 31330C START: SP_#STACK
0003 21000C0615 HL_#RAMZ; B_#RAMB-RAMZ;
0008 35002310FB (HL)_#0; INC HL; DBNZ .;
           set reflections
000D 21280113D0C HL_#INITT; DE_#INITR;
0013 011300EDB0 BC_#INITE-INITT; LDIR;
           initialise crt
0018 3E1ECD3B01 A_#FF; CALL CRT;

```

J STRT0;

```

0020 F5E5D5C32603 BREAKPOINT RESTART
0026 00 PUSH AF,HL,DE; J BPT1;
0027 00 NOP;
           NOP;

```

RST 5 = PRINT FOLLOWING STRING, TERMINATED BY 00

```

0028 E3 PRS: EX (SP),HL;
0029 7E23B7 PRS1: A,(HL); INC HL; TSTA;
002C 2805CD4A0C18F6 IF NZ; CALL $CRT; BR PRS1; FI;
0033 E3C9 EX (SP),HL; RET;

```

keyboard debounce delay routine

```

0035 AF KDEL: CLA;
0036 F5F1F5F13D20F9C9 PUSH AF; POP AF; PUSH AF; POP AF; DEC A; BR NZ .; RET;

```

```

003E CD4D0CD8 CHIN: read a char from keyboard or uart (first come first served)
0042 DB0217DE01D8 CALL $KBD; RET CS;
0048 18F4 IN A,2; RLA; IN A,1; RET CS;
           BR CHIN;

```

```

004A F5CD5300F11802 FLPLP: PUSH AF; CALL FLIP; POP AF; BR FLIP;
           set 0 reset a bit in I/O port 0

```

start or stop motor

```

0051 3E10 MOTFLP: A_#4;
           flip a bit in port 0
0053 E521000CAE FLIP: PUSH HL; HL_#PORT0; XOE (HL);
0058 D30077E1C9 OUT 0,A; (HL)_A; POP HL; RET;

```

put character out thru UART, and wait till sent

```

005D D301 SRL-OUT: OUT 1,A;
005F DB0287F818FA IN A,2; ADD A; RET M; BR .;

```

NOP; [padding]

NMI VECTOR

J \$NMI;

0066 C3470C

routine to read from keyboard
 carry is set if a char. is available
 the standard ASCII code for the char is returned in A
 EXCEPT FOR the following chars
 BS=16'1D backspace
 CR=16'1E carriage return (=newline)
 FF=16'1F form feed =clear screen

```

0069 C5D5E5      KBD:      PUSH BC,DE,HL;
006C 3E02CD4A00  A_#1; CALL FLFFLP;
0071 21010CDB002F77 HL_#KMAP; IN A,0; CMA; (HL)_A;
0078 0608      R_#8;
007A 3E01CD4A00  A_#0; CALL FLFFLP;
007F 23DB002F57AE2007  IN A,0; CMA; D_A; XOR (HL); BR NZ KSC2;
0087 10F1      KSC1A:  DBNZ KSC1;
0089 B7      KSC8:   TSTA;
008A E1D1C109   POP HL,DE,BC; RET;
008E CD3500      KSC9:   CALL KDEL;
0091 DB002F5F7AAE  IN A,0; CMA; E_A; A_D; XOR (HL);
0097 0EFF160037   C_#-1; D_#0; STC;
009C CB120C1F30FA  RL D; INC C; RRA; BR NC ;
00A2 7AA35F      A_D; AND E; E_A;
00A5 7EA2BB28DD   A_(HL); AND D; CMP E; BR Z KSC1A;
00AD 7EAA77      A_(HL); XOR D; (HL)_A;
00B1 3A010CE610B0  A_E; TSTA; BR Z KSC1A;
00B7 878787B1    A_KMAP; AND #*4; OR B;
00BB ED4B3F0C2A430CEDB1  ADD A; ADD A; ADD A; OR C;
                                BC_#KTAB; HL_#KTAB; CPIR;
                                check again for unshifted character
                                IF NZ;
00C4 280B      HL_#KTAB; BC_#KTAB;
00C6 2A430CED4B3F0C  AND #16'7F; CPIR;
00CD E67FEDB1    FI;
00D1 20E6      BR NZ KSC8;
00D3 ED4B430C37ED42  BC_#KTAB; STC; SBC HL,BC;
00DA ED4B410C097D  BC_#KTAB0; ADD HL,BC; A_L;
00E0 371BA7      KSC3:   STC; BR KSC9;

00E3 2A0C0C22150CC9  set breakpoint address
                                BREAK: HL_#ARC1; BRKADR_HL; RET;
    
```

table entries represent key number for each ASCII code appearing in ASCII order starting at code 16'1D. Each entry is in the format SRRRCCC where S=1 implies that shift key must be down RRRR=8-row number (number in counter) CCC=column number (bit number)

Setting all ones (16'FF) implies that there is no key for this code
 If the shift key is down and no code is found, then the table is searched again as if the shift key were up.

00EA 068809	KTAB:	.WORD 16'08,16'88,16'09;	[BS,	FF,	CR
00ED 149C9BA392C2BAB2		.WORD 16'14,16'9C,16'9B,16'A3,16'92,16'C2,16'BA,16'B2;	[SPACE	-	,
00F5 AAA298A0290A2119		.WORD 16'AA,16'A2,16'98,16'A0,16'29,16'0A,16'21,16'19;	[(-	/
00FD 1A1C1B2312423A32		.WORD 16'1A,16'1C,16'1B,16'23,16'12,16'42,16'3A,16'32;	[0	-	7
0105 2A221820E18AB999		.WORD 16'2A,16'22,16'18,16'20,16'B1,16'8A,16'B9,16'99;	[8	-	?
010D 0D2C41133E334310		.WORD 16'0D,16'2C,16'41,16'13,16'3B,16'33,16'43,16'10;	[@	-	C
0115 402D363028313925		.WORD 16'40,16'2D,16'38,16'30,16'28,16'31,16'39,16'25;	[H	-	O
011D 1D2415344535112B		.WORD 16'1D,16'24,16'15,16'34,16'45,16'35,16'11,16'2B;	[P	-	W
0125 443D3C		.WORD 16'44,16'3D,16'3C;	[X,	Y,	Z

RAM workspace area

```

0128 .RAM
0C00 RAMZ: [ this part cleared on RESET ]
0C00 PORT0: .BLKW; [ copy of output port 0 ]
0C01 KMAP: .BLKW 9; [ keyboard switch state table ]
      argument list set up by PARSE ]
0C0A ARGS: .BLKW 2;
0C0C ARG1: .BLKA;
0C0E ARG2: .BLKA;
0C10 ARG3: .BLKA;
0C12 NUM: .BLKW 3;

0C15 RAME: [ end of cleared RAM ]
0C15 BRKADR: .BLKA; BRKVAL: .BLKW;
0C18 CURSOR: .BLKA; [ CRT CURSOR ADDRESS
0C1A CONFLG: .BLKW;
0C1B .BLKA 12; [ Monitor's stack space ]
0C33 STACK: .BLKA;
0C35 .BLKA;
0C37 R.HL: .BLKA;
0C39 R.AF: .BLKA;
0C3B R.PC: .BLKA;
0C3D INITR: .BLKA;
0C3D R.SP: .BLKA;
      reflections
0C3F $KTABL: .BLKA; [ reflected length of KTAB ]
0C41 $KTABO: .BLKA; [ reflected offset to first character in KTAB ]
0C43 $KTAB: .BLKA;
0C45 $CTAB: .BLKA;
0C47 $NMI: .BLKW 3;
0C4A $CRT: .BLKW 3;
0C4D $KBD: .BLKW 3;

      .ROM;

      reflection initialisation table
0128 0010 INITT: .ADDR 16'1000; [ END OF RAM
012A 3E00 .ADDR 64+3-5; [ $KTABL ]
012C 1D00 .ADDR 32-3; [ $KTAB0 ]
012E EA006303 .ADDR KTAB, CTAB;
0132 C39503 J TRAP;
0135 C33B01 J CRT
0138 C36900 J KBD
013B INITE:

```

```

013B B7C8          CURTRAM=16'800; [ CRT ram addr ]
013D F5C5D5E5    CUR= '_'; [cursor character = underline]
0141 FE1E        BL=32; [space]
0143 202F        CR=31; [NEWLINE]
                   FF=30; [SHIFT+BS= CLEAR SCREEN]
                   BS=29; [BACKSPACE]

0145 21090336FF  CURLIN=CURTRAM+10<14*64>; [current CRT line]
014A 230630      LINE=CURLIN-64; [start of previous line]
                   Routine puts a char on screen
                   margins of screen contain zeroes except for top left
                   and bottom right which contain -1.
014D 36202310FB  FF initialises screen and puts cursor on bottom line
0152 0610       BS backspaces
0154 36092310FB  CR carriage returns and line feeds

0159 EB210A0E    CRT:  TSTA; RET Z; [ignore nulls]
015D 01B003EDB0  PUSH AF,BC,DE,HL;
0162 3EFF32BA0B  CMP #FF;
0167 218A0B      IF Z; [initialise screen]
016A 365F22180C  HL_*CURTRAM+9; (HL)_*-1;
016F E1D1C1F1C9  INC HL; B_*#48;
                   (HL)_*BL; INC HL; DBNZ .;
0174 2A180C3620  B_*#16;
                   (HL)_*0; INC HL; DBNZ .;
0179 FE1D        EX DE,HL; HL_*CURTRAM+10;
017B 200B        BC_*#15*64-16; LDIR;
                   CURTRAM<14*64>+58_*-1
017D 2B7EB728FB  HL_*CURLIN;
0182 3C20E5      CRT0:  (HL)_*CUR; CURSOR_HL;
0185 2318E2      CRT1:  POP HL,DE,BC,AF; RET;
0188 FE1F2809    CRT2:  FI;
                   [remove cursor]
                   HL_CURSOR; (HL)_*# ;
                   CMP #BS;
                   IF Z;
                   [backspace (thru margins if necessary)]
                   DEC HL; A_(HL); TSTA; BR Z .;
                   INC A; BR NZ CRT1;
                   INC HL; BR CRT1;
                   FI;
                   CMP #CR; BR Z CRT3;
                   [put char on screen, scroll if necessary]
                   (HL)_A;
                   INC HL; A_(HL); TSTA; BR Z .;
                   INC A; BR NZ CRT1;
                   [scroll]
                   DE_*CURTRAM+10; HL_*CURTRAM+10+64;
                   BC_*#14*64-16; LDIR;
                   HL_*#16;
                   ADD HL,DE; B_*#48;
                   (HL)_*BL; INC HL; DBNZ .;
                   DD ADDTG.

```

memory modify, arg1=address

```

01AD 2A0C0C      MODIFY: HL_ARG1;
01B0 CB3202      MOD1:  CALL TBCD3,
01B3 7ECD4402    A_(HL); CALL B2HEX;
01B7 CDD8011520B0600  CALL INLINE; DE_#LINE+8; B_#0;
                                note that line starts at LINE+8
01BF E5C05A02    MOD2:  PUSH HL; CALL NEXNUM;
01C3 7EB72808    A_(HL); TSTA; BR Z MOD3;
01C7 237EE17704  INC HL; A_(HL); POP HL; (HL)_A; INC B;
01CC 2318F0      INC HL; BR MOD2;
01CF E11AF2EC8   MOD3:  POP HL; A_(DE); CMP #'.'; RET Z;
01D4 78B729012318D5  IF B Z; INC HL; FI; BR MOD1;
    
```

print system prompt and read a line

```

01DB EF3E00      INLINE: RST 5; ">" ;
01DE CD3E00FE1D2809  INL0:  CALL CHIN; CMP #BS; BR Z INL2;
                                return on CR
01E5 FE1F2B57    CMP #CR; BR Z CRLF;
                                put out char and continue
01E9 CD4A0C18F0  INL1:  CALL $CRT; BR INL0;
                                handle backspace; dont allow backspace over prompt
01EE ED5B189C1B1AFE3E  INL2:  DE_CURSOR; DEC DE; A_(DE); CMP #'>;
01F6 2BE63E1D18ED  BR Z INL0; A_#BS; BR INL1;
    
```

tabulate code. ARG1=start addr, ARG2=end
 routine is used by Dump command

```

01FC 2A0C0C      TABCDE: HL_ARG1;
01FF ED5B0E0CE5B7ED52  TBCD1:  DE_ARG2; PUSH HL; TSTA; SBC HL,DE;
0207 E18B05EF2E1F00C9  POP HL; IF CC; RST 5; " ",CR; RET; FI;
020F 0E00CD32020608  C_#0; CALL TBCD3; B_#8;
0216 7ECD2B0223    TBCD1A: A_(HL); CALL TBCD2; INC HL;
                                CALL SPACE; DBNZ TBCD1A;
                                put out checksum and backspace over it so it doesnt show
0220 79CD4402      A_C; CALL B2HEX;
0224 EF1D1D1F00    RST 5; .WORD BS,BS,CR,0;
0229 1804          BR TBCD1;
022B 57814F7AC34402  TBCD2: D_A; ADD C; C_A; A_D; J B2HEX;
0232 7CCD2B02      TBCD3:  A_H; CALL TBCD2;
0236 7DCD2B021800  A_L; CALL TBCD2; BR SPACE;

023C 3E201817      SPACE:  A_#'; BR JCRT;
0240 3E1F1813      CRLF:  A_#CR; BR JCRT;

                                print A in hex
0244 F51F1F1F1F      B2HEX:  PUSH AF; RRA; RRA; RRA; RRA;
0249 CD4D02F1      CALL B2HEX1; POP AF;
024D E60FC630      B2HEX1: AND #16'F; ADD #'0;
0251 FE3A3802C607  CMP #'9+1; IF CC; ADD #'A-'0-10; FI;
0257 C34A0C      JCRT:  J $CRT;
    
```


read in a hex number, DE being used as pointer to line
 NUM+1, NUM+2 contain the number
 NUM set non zero if there is a number there at all

```

025A 1AFE201328FA1B NEXNUM: A(DE); CMP #' ; INC DE; BR Z ; DEC DE;
0261 AF211120C CLA; HL_#NUM;
0265 7728772877 (HL)_A; INC HL; (HL)_A; INC HL; (HL)_A;
026A 1A2B2B A_(DE); DEC HL, HL;
026D D630F8 SUB #'0; RET M;
0270 FE0A3808 CMP #10; BR CS NN2;
0274 D607 SUB #'A-'0-10;
0276 FE0AF8 CMP #10; RET M;
0279 FE10F0 CMP #16; RET P;
027C 133423ED6F INC DE,(HL),HL; RLD;
0281 23ED6F INC HL; RLD;
0284 18E4 BR NN1;
    
```

main monitor loop; read a line and obey it

```

0286 C00B01 PARSE: CALL INLINE;
0289 114B0B010A0C1A DE_#L,NE+1; BC_#ARGS; A_(DE);
0290 FE20 CMP #' ; [ CHECK FOR STEP REPEAT]
0292 20950AFE5320ED IF Z; A_(BC); CMP #'S; BR NZ PARSE; FI;
0299 020813AF02 (P)_A; INC BC,DE; CLA; (BC)_A;
    get the arguments
029E 03CD5A02 PLOOP: INC BC; CALL NEXNUM;
02A2 7EB7280D A_(HL); TSTA; BR Z PEND;
02A6 237E022303 INC HL; A_(HL); (BC)_A; INC HL,BC;
02AB 7E02 A_(HL); (BC)_A;
02AD 210B0C3418EB HL_#ARGS+1; INC (HL); BR PLOOP;
02B3 ED4B0A0C2A450C BC_#ARGS; HL_#CTAB;
02BA 7EB728C8 PEND: A_(HL); BR A Z PARSE; [no such command]
02BE 23 INC HL;
02BF B9 CMP C;
02C0 2805 IF NZ;
02C2 00 NOP; [patch]
02C3 232318F3 INC HL,HL; BR PEND1;
02C7 F1;
02C7 5E2356 E_(HL); INC HL; D_(HL);
02CA 218602E5EBE9 HL_#PARSE; PUSH HL; EX DE,HL; J (HL);
    
```

execute command, if arg supplied then this is start address

```

02D0 3EFF321A0C EXEC: CONFLC_#-1;
common to E and S, conflag tells which
set NMI for end of instr
02D5 21050322480C EXEC1: HL_#TRAP; $NMI+1_HL;
02DB E1 POP HL; [RUBBISH]
02DC 3A0B0CB72806 IF ARG$+1 NZ;
02E2 2A0C0C223B0C HL_ARG1; R_PC_HL;
02E8 FI;
02EB C1D1F1F1 POP BC,DE,AF,AF;
02EC 2A3D0CF9 HL_R.SP; SP_HL;
02F0 2A3B0CE52A370C HL_R.PC; PUSH HL; HL_R.HL;
02F7 F53E08D300 PUSH AF; OUT 0,**3;
02FC F1ED45 POP AF; RETN;

```

step, if arg supplied then this is address

```

02FF AF321A0C18D0 STEF: CLA; CONFLC_A; BR EXEC1;

0305 F333E3 TRAP: EX (SP),HL; INC HL; EX (SP),HL;
0308 F5E5 PUSH AF,HL;
030A 3A000CD300 OUT 0,PORT0;
030F 3A1A0CB72810 IF CONFLC_NZ;
0315 2A150C7E32170C HL_BRKADR; A_(HL); BRKVAL_A;
031C 36E7 (HL)_#8'347; [RST 4]
031E E1F1E32BE3 POP HL,AF; EX (SP),HL; DEC HL; EX (SP),HL;
0323 ED45 RETN; FI;
0325 D5 PUSH DE;
0326 C521000039 PUSH BC; HL_#0; ADD HL,SP;
032B 11380C DF_#STACK;
032E 31330C010800EDB0 SP_#STACK; BC_#8; LDIR;
0336 5E23 E_(HL); INC HL;
0338 56231B D_(HL); INC HL; DEC DE;
033B ED533E0C223D0C R_PC_DE; R_SP_HL;

```

print out regs SP PC AF HL DE BC:

```

0342 213F0C0606 HL_#R.SP+2; B_#6;
0347 2B7ECD4402 DEC HL; A_(HL); CALL B2HEX;
034C 2B7ECD4402 DEC HL; A_(HL); CALL B2HEX;
0351 CD3C02 CALL SPACE;
0354 10F1 DBNZ RECS1;
0356 CD4002 CALL CRLF;
0359 2A150C3A170C77 HL_BRKADR; A_BRKVAL; (HL)_A; [RESTORE BREAKPOINT]
0360 C38602 J PARSE;

```

command table
 format: character, address of subroutine

CTAB: .WORD 'M'; .ADDR MODIFY;
 .WORD 'C'; .ADDR COPY;
 .WORD 'E'; .ADDR EXEC;
 .WORD 'S'; .ADDR STEP;
 .WORD 'T'; .ADDR TABCDE;
 .WORD 'B'; .ADDR BREAK;
 .WORD 'L'; .ADDR LOAD;
 .WORD 'D'; .ADDR DUMP;
 NOP;

load command

LOAD: CALL MOTFLP; [start motor]
 LOD1: HL_#CURLIN; CURSOR_HL;
 LOD1B: CALL CHIN; CMP #BS; BR Z .;
 CMP #CR; BR Z LOD1A;
 LOD1A: CALL \$CRT; BR WZ LOD1B;
 DE_#CURLIN; B_#B;
 A_(DE); CMP #.; J Z MOTFLP;
 CALL NEXNUM; HL_NUM#+1;
 A.; ADD H; C_A;
 PUSH HL; HL_#CRTRAM [TEMP BUFFER IN FIRST 8 WORDS]; PUSH HL;
 LOD2: PUSH HL; CALL NEXNUM; INC HL; A_(HL);
 POP HL; (HL)_A; INC HL; ADD C; C_A; DBNZ LOD2;
 CALL NEXNUM; INC HL; A_(HL); CMP C;
 POP HL,DE;
 IF Z;
 BC_#B; LDIR; BR LOD1;
 FI;
 CALL ORLF; BR LOD1;

DUMP, uses same code as TABULATE

DUMP: CALL MOTFLP;
 B_#0;
 CALL KDEL; DBNZ .;
 HL_#CRT+1; PUSH HL;
 HL_#SRLOUT; \$CRT+1_HL;
 CALL TABCDE;
 POP HL; \$CRT+1_HL;
 J MOTFLP;

copy, arguments:from, to, length

COPY: HL_ARG1; DE_ARG2;
 BC_ARG3; LDIR;
 RET;
 .BLKZ 16'400-.; [PAD OUT TO END OF ROM]
 .END START
 0400

ARCS :0C0A	LOD1B :0385
ARG1 :0C0C	LOD2 :03AE
ARG2 :0C0E	MODIFY:01AD
ARG3 :0C10	MOD1 :01B0
BL =0020	MOD2 :01BF
BPT1 :0326	MOD3 :01CF
BREAK :00E3	MOTFLP:0051
BRKADR:0C15	NEKNUM:025A
BRKVAL:0C17	NN1 :026A
BS =001D	NN2 :027C
B2HEX :0244	NUM :0C12
B2HEX1:024D	PARSE :0286
CEIN :003E	PEND :02B3
CONFLG:0C1A	PEND1 :02BA
COPY :03EF	PLOOP :029E
CR =001F	PORT0 :0C00
CRLF :0240	PRS :0028
CRT :013B	PRS1 :0029
CRTRAM=0800	RAME :0C15
CRV0 :0167	RAMTOP:0C50
CRT1 :016A	RAMZ :0C00
CRT2 :016F	RAM. =0C50
CRT3 :0195	REGS1 :0347
CTAB :0363	ROMTOP:0400
CUR =005F	ROM. =0128
CURLIN=0B8A	R.AF :0C39
CUSOR:0C16	R.HL :0C37
DUMP :03D1	R.PC :0C3B
EXEC :02D0	R.SP :0C3D
EXEC1 :02D5	SPACE :023C
FF =001E	SRLOUT:005D
FLIP :0053	STACK :0C33
FLPFLP:004A	START :0000
INITE :013B	STEP :02FF
INTR :0C3D	STRT0 :0359
INITT :0128	TABCODE:01FC
INLINE:01DB	TBCD1 :01FF
INL0 :01DE	TBCD1A:0216
INL1 :01E9	TBCD2 :022B
INL2 :01EE	TBCD3 :0232
JCRT :0257	TRAP :0305
KBD :0069	\$CRT :0C4A
KDEL :0035	\$CTAB :0C45
KNAP :0C01	\$KBD :0C4D
KSC1 :007A	\$KTAB :0C43
KSC1A :0087	\$KTABL:0C8F
KSC2 :008E	\$KTAB0:0C41
KSC3 :00E0	\$NMI :0C47
KSC8 :0089	. =0400
KSC9 :008A	
KTAB :00EA	
LINE =0B4A	
LOAD :037C	
LOAD1 :037F	

PART 18. HOW TO USE AND PROGRAMME YOUR NASCOM 1

SECTION A: HOW TO USE THE NASCOM 1

1. See page 3 of the handbook: 'Important notes for all NASCOM users'.
2. Ensure power supply voltages are correct before connecting to NASCOM 1. (Borrow a meter if necessary).
3. It is not advisable to switch the power supplies at low voltage as some devices (e.g. character generator and EPROM) can be destroyed by a momentary absence of the -5V supply. If it is necessary to switch the low voltage supplies they must be sequenced so that the -5V supply is always switched on first (before either of the positive supplies) and switched off last. This problem is avoided with mains supply switching due to the gradual rise and fall of the low voltages ensured by the large electrolytic capacitors incorporated in the smoothing circuits.
4. When the system is operating and the TV set tuned in, run through the NASBUG command examples in part 16 and in Section E of this part of the handbook. You can then try your own hand at programming or enter programmes obtained from any source.
5. If you wish to add further peripherals to your system see the following Section B and all relevant technical handbooks.
6. If you are new to computers see Section C and any good textbooks for further fundamentals.
7. If you wish in future to use a high level language or an assembler with your NASCOM 1 see Section D and the latest NASCOM product announcements.
8. Please join the International Nascom Users' Club and let us know any problems, constructive criticisms, hardware and software ideas you may have, any requests for future products and any interesting uses you have found for your NASCOM 1.

SECTION B: PERIPHERAL HARDWARE

Developments both in the semiconductor industry and in home computing are occurring at such a rate that these notes can only act as a pointer to the possibilities that exist for the experimenter. (See our seminar notes for some ideas).

However powerful a computer may be its usefulness is governed vitally by the interfaces through which it communicates with the user and with the real world. Without further specialised equipment the basic NASCOM 1 provides visual display of 768 characters on a video monitor or domestic TV set, a serial interface for programme or data storage on a domestic tape recorder, 16 parallel input/output lines (at 5V, TTL level) as well as a solid-state alphanumeric keyboard.

Although no specific tape recorder is recommended some useful points can be made. The NASCOM 1's simple 'cassette' interface relies on the presence or absence of a signal and can therefore be misled by tape dropouts or spurious interference. We therefore advise the use of the thickest tape (C60) from a reliable manufacturer. (A C60 tape can store some 85K Bytes of data or 20K bytes using the standard dump format). There is no need for ultra-low noise or CrO2 hi-fi tape. In addition great care should be taken to keep the tape heads and drive capstan clean and clear of oxide particles. All hi-fi stores sell tape head maintenance kits.

Any tape recorder, whether cassette or reel to reel, may be used. However a machine with a tape position counter is strongly advised as an aid to locating recorded data. The only argument in favour of a more expensive hi-fi deck is that the mechanism is less likely to wrinkle the tape and better speed control is probable. A stereo cassette deck should be operated in the mono mode, as there is too little separation between tracks to make separate recordings on each channel.

As an alternative, the serial I/O circuitry may be adjusted (using links LK 2, 3 & 4) to provide the standard 20mA loop interface with a Teletype or the standard RS232 interface with an external VDU, serial keyboard, etc. all via the 16 pin SK2. By altering connections to the UART control inputs (See Data Sheet provided) the serial interface may be used with a Baudot 5 bit code teleprinter. If an external clock signal for the UART (at 16 times the bit rate) is fed in via LK4, then data transfers may occur at any rate up to 200K baud. Any of these alternatives will need short driving programmes in order to perform transmission and interpretation of control signals as may be desired. If cassette operation is also wanted on the same unit, then either a multipole switch, relay or digital switch (e.g. CMOS 4016) could be wired in place of the links.

On a more mundane level there are few alternatives to be considered for the TV interface. The figure of 48 characters per line was considered the maximum legible on a domestic receiver. Experience has shown some difference between individual receivers, due to their various video IF

(Intermediate Frequency) responses. A colour TV set is not advised as the colour dot or stripe pattern combined with any convergence errors will render the characters less distinct. The NASCOM 1 may however be used with receivers built for virtually any colour or transmission standard in the world (except the old 405 line system) providing the tuner will receive UHF bands 4 and 5. A VHF only receiver could probably be used if the modulator fundamental frequency were reduced, e.g. by adding a turn or two to coil L1. Although intended for use with the 625 line 50Hz system, the NASCOM 1 could be used with a 525 line 60Hz receiver in North/South America or Japan if the picture height were reduced as the line frequencies are virtually identical.

If a receiver is purchased specially with the NASCOM 1 in mind, a small modern black and white portable with rectangular screen is the best answer. However, if perfect picture quality is necessary a video monitor is the only ideal solution. We do not advise anyone to attempt to convert a TV receiver to accept a video input unless they are fully aware of the dangers involved and are experienced in repairing TV sets. It is to be hoped that a video input will soon become a common feature of new receivers.

The 16 parallel input/output lines (and 4 associated control lines) available can be connected via suitable buffering circuitry to any device the user may provide. As inputs they can accept any data in digital form such as time of day/date from a clock system, ASCII code from a separate parallel connected keyboard, analogue data (such as temperature) after A/D conversion or simple connection to an on/off switch or sensor for each line. As outputs they can for example feed a parallel connected printer for hard copy output, control light levels via D/A converters and thyristor dimmers or provide information on 7-segment LED displays. The PIO Controller can be operated in various different modes as may be most convenient. For example, data can be read by the CPU from the parallel ports either by regular scanning of the port status or by the automatic generation of an interrupt when data is available. See the PIO technical manual for further details. Note also that two bits of Port 0 are available to the user in both directions.

In future, through the standard bus interface, the user will be able to plug into his system memory and I/O expansion cards (which we will be making available) or standard prototyping cards containing any circuitry he may desire. In this manner, virtually any number of additional serial or parallel interfaces and special purpose devices, such as the Z-80 CTC (Counter/Timer Controller), can easily be accommodated.

SECTION C: COMMUNICATING WITH THE COMPUTER

By itself the microprocessor or its equivalent at the heart of a large computer is not a useful device. If an array of switches and indicators is connected to all the address, data and control lines then the internal read/write memory (the Registers) and the specified set of instructions

for the device can be tested and confirmed to work
(assuming it can be made to operate
with a clock period of several seconds.)

At the next level, a real system dedicated to one particular purpose (such as the recently available single chip microcomputers) must contain some Read Only Memory (ROM) for programme storage and I/O lines to interface with the outside world (and may also need a small RAM scratchpad memory if the internal registers provide insufficient temporary storage). Such a device may be used to control a washing machine, a burglar alarm, an electronic calculator or a peripheral device in a larger computer system. It is, however, totally inflexible, as its internal programme will perform that one task only.

A microcomputer such as the NASCOM 1 gains its flexibility from the provision of a larger amount of Random Access or Read/Write Memory (RAM), to store any programme or data, convenient peripheral interfaces for the user, facilities to expand memory or peripherals virtually without limit and a monitor programme (or 'BUG') in ROM to tie the whole into a system. At its simplest, the latter may comprise a 'bootstrap loader' that merely enables data fed into a particular peripheral to be loaded into sequential locations in RAM. In our case, however, the NASBUG monitor in EPROM provides a comprehensive operating system that controls the keyboard, serial interface, video/TV display, programme entry, modification, execution and de-bugging. Thus we have a computer capable not only of performing any one or more of the functions mentioned above but also useful as a development aid in the design of any system dedicated to a particular purpose.

So far however all these units are controlled or programmed by the user in the only language that they are designed to obey: this is called machine code and comprises digital 'words' of 8 bits (1 byte) for the Z80 (although computers may use any word length e.g. 4, 8, 12, 16, 24, 32 or more bits). For our own convenience we represent these 8 binary digits in written form using 2 digits of hexadecimal code. Thus a word of 8 bits is split into 2 groups of 4 bits which are then each replaced by a single digit representing a number in the range of 0 to 15. A mixture of letters and numbers are used in hexadecimal code as shown below:-

<u>BINARY</u> (Number Base two)	<u>DECIMAL</u> (Base Ten)	<u>HEXADECIMAL</u> (Base Sixteen)
0000	0	0
0001	1 (= 2^0)	1
0010	2 (= 2^1)	2
0011	3	3
0100	4 (= 2^2)	4
0101	5	5
0110	6	6
0111	7	7
1000	8 (= 2^3) $\{2^3\}$	8
1001	9	9
1010	10	A
1011	11	B
1100	12	C
1101	13	D
1110	14	E
1111	15	F

<u>BINARY</u>	<u>DECIMAL</u>	<u>HEXADECIMAL</u>
(Number Base Two)	(Base Ten)	(Base Sixteen)

Further examples:

		0001 0000 (1 byte)	16 ($= 2^4$)	10
		0001 0001	17	11
		0001 1000	24	18
		0001 1111	31	1F
		0010 0000	32 ($= 2^5$)	20
		0011 0000	48	30
		0100 0000	64 ($= 2^6$)	40
		0110 0100	100	64
		1000 0000	128 ($= 2^7$)	80
		1100 1000	200	C8
		1111 1111	255	FF
0000	0001	0000 0000 (2 bytes)	256 ($= 2^8$)	100
0000	0001	1111 0100	500	1F4
0000	0010	0000 0000	512 ($= 2^9$)	200
0000	0011	1110 1000	1000	3E8
0000	0011	1111 1111	1023	3FF
0000	0100	0000 0000	1024 ($= 2^{10}$ or 1K)	400
0000	0111	1101 0000	2000	7D0
0000	1000	0000 0000	2048 ($= 2^{11}$ or 2K)	800
0001	0000	0000 0000	4096 ($= 2^{12}$ or 4K)	1000
0010	0000	0000 0000	8192 ($= 2^{13}$ or 8K)	2000
0100	0000	0000 0000	16384 ($= 2^{14}$ or 16K)	4000
1000	0000	0000 0000	32768 ($= 2^{15}$ or 32K)	8000
1111	1111	1111 1111	65535	FFFF

ditto plus 1: (3 bytes)65536($= 2^{16}$ or 64K)10000

(Any Hexadecimal number may appear in documents with a suffix 'H' in order to avoid confusion. E.g. 16 = 10H. Note also that computer terminals, printers, keyboards and display devices usually distinguish between the letter 'O' (which has no numerical meaning) and the digit zero by adding a stroke through the middle of the digit thus: 'Ø'. Typewriters do not usually have this facility, but no confusion is normally likely to arise. In manuscript, however, many programmers prefer to add the stroke for clarity).

One of the most vital functions provided by the NASBUG operating system therefore is to convert Hexadecimal code pairs typed on the 16 relevant keyboard keys into 8 bit bytes and enter these into memory. We have, therefore, a system which we can programme (and into which we can load data) in the hexadecimal representation of machine code. We can call this Object Code (or, more loosely, machine language).

SECTION D: ALTERNATIVE PROGRAMMING LANGUAGES

Although at the deepest level every computer can only operate in its own machine language (and every different CPU has its own language) there are numerous advantages to be gained from programming the computer (in machine code) to communicate with the user in a language more nearly compatible with everyday human speech or specialist mathematical functions (with numbers in the decimal system). There are many such so called 'High Level' languages in use, each with its own adherents and each with its advantages and disadvantages. Among the widespread high-level languages are BASIC,

FORTRAN, COBOL (specially intended for business use), APL (Scientific), PL/1 and many more. Their most notorious feature is the way that each user and each computer manufacturer tend to diverge slightly from the standard (if any is laid down) so that a programme in, say, BASIC written for one machine may require subtle editing before it will work on another, due to a small difference in dialects. In general, however, they are a boon as they enable a programmer to write his programmes in a language that can be run (with luck first time) on any computer fitted with a compiler or interpreter to convert that high level language across into that particular machine's low-level language.

The NASCOM 1 memory expansion board has facilities provided to accept a 2K 'TINY BASIC' Interpreter in EPROM which will enable users to become acquainted with the essentials of BASIC programming. Plans have already been announced for a powerful 16K BASIC to be made available later.

Intermediate, between the low level machine language and the various high level languages, is the "ASSEMBLY LANGUAGE" or Source Code specific to each machine. For the convenience of programmers the manufacturer specifies for each machine language instruction (or Opcode) a more easily memorable 'mnemonic' code. For example for the Z80 we have:-

<u>MNEMONIC</u>	<u>MEANING</u>
LD	Load
EX	Exchange
HALT	Halt awaiting interruptor RESET.
IN	Accept data from peripheral port.
JP	Jump to another part of the programme.

(etc.)

Following the mnemonic we may have an OPERAND such as a register, a number, a memory location etc. For full details of the mnemonic codes, operands and addressing modes available see the Z80 Technical and Programming manuals.

If we do not have a high level language facility available or do not wish to use a high level language in order to economise on memory usage (or because the application is more suited to low level language programming) then we will be working in Assembly Language.

We therefore list the mnemonics and operands and then (using the tables in the Z80 handbooks) convert them into a parallel list of Hexadecimal Object Code. For lengthy programmes this procedure can become tedious, and so a programme called an Assembler can be used to perform the conversion for us. There are various types; from a simple interpreter that converts mnemonic code into object code directly; to multipass compilers that make sophisticated use of labels for subroutines etc. For those who require such facilities we will be making a powerful assembler available shortly.

The remainder of this guide shows how to programme the basic NASCOM 1 in Z80 machine language, using the peripherals provided.

SECTION E: PROGRAMMING THE NASCOM 1

1: Preliminary

Upon switch-on the NASCOM 1 enters a random state similar to the result of a programme that has run wild. The screen will be full of arbitrary characters, one or two of the LED indicators may be lit and there will be no response to the keyboard (except for the RESET key). In order to bring the monitor programme into operation it is necessary to operate the RESET key (which causes the CPU to Jump to the instruction at 0000; i.e. the first byte stored in the NASBUG monitor EPROM).

<u>ACTION</u>	<u>RESULT</u>
RESET	LED's turned off. Screen Cleared (except perhaps for one arbitrary character placed by breakpoint routine). PROMPT (>) and CURSOR (_) printed in bottom left hand corner.

The system is now executing a programme loop that scans the keyboard (providing software debounce and Hex code allocation via a look-up table) and also the UART for any serial input data. Any such data from either source is displayed in the next available screen position.

Before proceeding further, however, it is necessary to complete system initialisation by placing the breakpoint location out of harm's way (i.e. out of RAM). The standard procedure is to place the breakpoint at location 0000 as follows:-


```
ACTION  
BO NL  
ED  
NL
```

The user may now proceed to type any of the available keyboard characters on the screen and use any of the 8 monitor commands.

2. Keyboard Characters

The standard keyboard and monitor look-up table provide the following characters and control functions:

RS (Reset Key)



N A S C O M 1 K E Y B O A R D L A Y O U T

(SHOWING SHIFTED CHARACTER ALLOCATIONS)

If the SHIFT key is depressed together with a key for which no shifted character is allocated then the unshifted character will be displayed. If several keys are depressed together each of the characters will be displayed in an arbitrary order. If an attempt is made to place 48 or more characters in a line an upward scroll is automatically performed and the cursor moved to the bottom left hand corner.

One or more characters may be deleted and the cursor moved left by use of the BACKSPACE key. Backspacing is inhibited by the PROMPT (>) symbol however if this does not appear at the start of a line then BACKSPACE will move the cursor to the right hand end of the line above. The ultimate limit is the left hand end of the fifteenth line up.

The screen may be cleared (including the unscrolled top line) by use of the SHIFT and BACKSPACE keys together. This places the CURSOR in the bottom left hand corner but does not issue a PROMPT symbol, so the NEWLINE key must be pressed before issuing a monitor command.

The NEWLINE (NL) key causes the contents of each of the bottom 15 lines to be scrolled up by one line (the top line of the 15 being lost) and the PROMPT and CURSOR symbols to be issued at the start of the cleared bottom line. This key is the most important of all, as it also performs the 'Enter Command' function, providing one of the 8 command characters is next to the PROMPT symbol in the bottom left hand corner.

If for any reason (e.g. use as a video typewriter for message display) it is desired to inhibit the monitor commands, one or more spaces should always be inserted between the PROMPT symbol and the first character. (Alternatively, a simple programme can have the same effect).

3. Monitor Commands

(For full details and examples see part 16 of this handbook).

M	Inspect/Modify memory contents. (Used for entering user programmes). - Terminated by a full stop.
T	Tabulate memory contents.
D	Dump from memory to serial interface (for cassette, etc.)
L	Load from serial interface to memory. (May be terminated by "NL full stop NL NL" if no full stop read off tape).
C	Copy memory contents from one section of memory to another.
B	Set breakpoint in user programme.
E	Execute programme.
S	Single step through programme. (Terminated by a different command or a full stop).

When a breakpoint is met (or when single stepping) six register pairs are displayed on the screen as follows:-

SP PC AF HL DE BC

To display register contents at any time the command S3FF NL (single step through a 'NOP' instruction) may be used.

The S command may be used to single step through programmes either in ROM (EPROM) or RAM and so can be used to demonstrate monitor routines (except for part of the keyboard scanning routine where lock-out will occur).

Initial Data or Address zeroes may be omitted so that the following commands are identical in effect:-

TD 5F = T0000 005F

When single stepping from a location other than the start of a programme beware of making illegal demands on the Stack Pointer. Never single step through a 'RET' or 'POP' instruction unless the corresponding 'CALL' and 'PUSH' instructions have previously been obeyed.

If in any doubt where the breakpoint is located check the contents of locations 0C15 and 0C16 (the least significant byte is first). Normally these will both contain zeroes if the breakpoint was last set at location 0000 (as during system initialisation).

If in any difficulty use the RESET key to regain control.

If a programme has gone wrong you may either single step from the start to see the point at which any register contents differ from those expected or move a breakpoint progressively through the programme until the trouble spot is isolated.

4. Programme Development Example

Aim: To display on the screen in table form (as on page 33) the full character set available from the character generator.

Method: We will dive straight into the problem. (Those who find flowcharts clarify the reasoning will find it instructive to draw their own. Consult textbooks/magazine articles if further information is required).

Stage

Comments

(a) We must initialise any registers that are to act as pointers to Memory (or the screen) or to contain a constant for loop counting, etc. We will not know what initialisation is needed or the order in which it must appear until we have considered the next two stages:

Stage

Comments

- (b) The programme will contain one basic loop in which VDU RAM location has a character code written into it and then the pointer is moved on to the next location.
- (c) We must then test the pointer location (or some other parameter) to see if we have completed a line. Instead of looping back in the programme to write the next character we must first shift the pointer to the start of the next line and then loop back to a point in the initialisation routine that will cause a new line to be written. If we have reached the end of the table we must decide how to end the programme.
- (d) Consider item (b). The obvious 'write' instruction (if we choose not to use subroutines in the monitor programme) is "LD (HL), A". We therefore use the HL register pair to point to VDU RAM memory locations and the accumulator (the A register) to contain the character code. If we space out the table roughly to fill the top half of the screen we must move the pointer right 3 spaces for the next position.

Thus the core of the programme is:-

```
LD (HL), A      Write character on screen.
INC A           Code for next character.
INC HL          }
INC HL          }
INC HL          }      Move pointer to next location.
```

- (e) Consider item (c). DJNZ is a convenient 'test and loop' instruction and it uses the B register. We must therefore precede the main loop with an initialisation instruction to set the number of characters per line:

```
LINE: LD B, 10H (10H = 16 Decimal).
```

After the main loop we will have:

```
DJNZ - 05H      If B not zero decrement B and jump
                back 5 places to the location labelled
                "WRITE" (We know the previous 5
                instructions each comprise a single byte).
```

A convenient method of shifting the pointer to the start of the next line (rather than e.g. using INC HL sixteen times) is to store 16 (or 10H) in the DE register (as it is not needed elsewhere) and add it to HL thus:-

```
ADD HL,DE
```

We must now detect the end of the table. We can do this either by testing the character code in A or the pointer location in HL. If we use the former method:-

```
CP 80H          Detect 129 th. character (1st was 00H).
```

We must then loop back to location "LINE" if A does not contain 80H thus:-

```
JRNZ "LINE"      Jump back to line if zeroflag
                  not raised (we can insert the
                  actual jump offset when converting
                  to object code subsequently).
```

We can then end the programme in one of several ways. We could use:

```
HALT
```

to light the 'HALT' LED and leave the CPU in effect executing a continuous series of NOP's. We could only exit from this however using RESET (or a peripheral interrupt if so programmed). We could call the KBD routine and test for particular key pressings to branch to any other programmes. The most useful ending however is jump back into the main monitor loop ("PARSE") using:-

```
JP 0286 H
```

We can then use any of the 8 monitor commands as was the case before the programme was executed.

- (f) We can now list the complete programme with object code and initialisation routines. (The labels and comments are provided for guidance only). The locations shown for entering the programme are quite arbitrary as it contains no absolute jumps or calls and may be placed anywhere in User RAM.

TO DISPLAY CHARACTER SET ON SCREEN

<u>LOCATION</u>	<u>OBJECT CODE</u>	<u>LABEL</u>	<u>SOURCE CODE</u>	<u>COMMENT</u>
OCE0	11 10 00	START	LD DE,0010H	Width of margin.
OCE3	21 0B 08		LD HL, 080BH	Near top left of screen.
OCE6	3E 00		LD A, 00H	First character code.
OCE8	06 10	LINE	LD B, 10H	Characters per line.
OCEA	77	WRITE	LD (HL), A	Write character.
OCEB	3C		INC A	Code for next character.
OCEC	23		INC HL	Move pointer right 3 places.
OCED	23		INC HL	
OCEE	23		INC HL	
OCEF	10F9		DJNZ-5H	Jump to WRITE if line not ended.
OCF1	19		ADD HL,DE	Start of next line.
OCF2	FE 80		CP 80H	Test for end of table.
OCF4	20F2		JRNZ -CH	Jump to LINE if not.
OCF6	C3 86 02		JP 0286H	Jump to PARSE in NASBUG.

- (g) The object code programme is entered using the M instruction as shown in part 16 of this handbook.

- (h) It may then be tabulated using the T command thus:-

```
TCE0 CFF
      NL
```

and checked for any obvious mistakes.

- (i) The S command may then be used to single step through the start of the programme to check that the registers are being manipulated correctly.
- (j) The B instruction may be used to set a breakpoint in the main loop. For example:-
- ```
BCEB NL
```
- (k) The programme can be executed up to the breakpoint (A'B' instruction must be followed by an 'E' instruction in any case). The starting location is 0CE0 so we type:-
- ```
ECE0 NL      (or E0CE0 NL)
```
- (l) We can then either use S to single step to check that the relative jump offsets are correct or type simply:-
- ```
^NL
```
- to pass round the loop once and return to the breakpoint. As stated earlier 6 major register pairs are displayed after each breakpoint or single step in order that any problem may be analysed.
- (m) We can move the breakpoint elsewhere if desired (for example to 0CF1 at the end of one character row).
- (n) We can remove the breakpoint:-
- ```
B0 NL
```
- (o) And then execute the programme normally:-
- ```
ECE0 NL
```
- (p) Note that a routine to clear the screen could be added at the start (See Section F).
- (q) Due to the monitor's scrolling action, the character table will not remain on the screen while single-stepping or using the breakpoint.
- (r) In order to become familiar with programming the user may next wish to modify or 'improve' the above programme. (For example to display a narrower table, to display only part of it or to re-locate it on the screen).

5. A Further Example Programme

Aim: To display the full character set as before but with a variable delay routine between 'write' instructions.

Execute Codes { ED00<sub>NL</sub> to cycle every minute or so (Exit via RESET)  
ED08<sub>NL</sub> to write once and then return to monitor.

TO WRITE CHARACTER SET SLOWLY

| <u>LOCATION</u> | <u>OBJECT CODE</u> | <u>LABEL</u>   | <u>SOURCE CODE</u> | <u>COMMENTS</u>                                                         |
|-----------------|--------------------|----------------|--------------------|-------------------------------------------------------------------------|
| 0D00            | CD 10 0D           | START A        | CALL 0D10H         | Call subroutine.                                                        |
| 0D03            | CD 12 0D           |                | CALL 0D12H         | Call Sub.2 (Clear).                                                     |
| 0D06            | 18 F8              |                | JR -6H             | Back to Start.                                                          |
| 0D08            | CD 10 0D           | START B        | CALL 0D10H         | Call subroutine.                                                        |
| 0D0B            | C3 86 02           |                | JP 0286H           | Jump to monitor.                                                        |
| 0D0E            | 00 00              |                | NOP, NOP           | (Padding).                                                              |
| 0D10            | 0E 80              | SUB<br>ROUTINE | LD C,80H           | 1st character (plus 80H.)                                               |
| 0D12            | 11 10 00           | SUB.2          | LD DE,0010H        | Width of margin.                                                        |
| 0D15            | 21 08 08           |                | LD HL, 0808H       | Near top left of screen.                                                |
| 0D18            | 06 10              | LINE           | LD B, 10H          | Characters per line.                                                    |
| 0D1A            | 71                 | WRITE          | LD (HL),C          | WRITE character.                                                        |
| 0D1B            | 79                 |                | LD A,C             | } Test for space code.                                                  |
| 0D1C            | FE 20              |                | CP 20H             |                                                                         |
| 0D1E            | 28 01              |                | JR Z,+ 3H          | } Choose next character if not clearing screen.                         |
| 0D20            | 0C                 |                | INC C              |                                                                         |
| 0D21            | 23                 |                | INC HL             | } Move right 3 places.                                                  |
| 0D22            | 23                 |                | INC HL             |                                                                         |
| 0D23            | 23                 |                | INC HL             | } Variable delay depending on Register C, i.e. character being written. |
| 0D24            | 79                 |                | LD A,C             |                                                                         |
| 0D25            | 08                 |                | EX AF,AF'          |                                                                         |
| 0D26            | AF                 |                | XOR A              |                                                                         |
| 0D27            | 3D                 |                | DEC A              |                                                                         |
| 0D28            | 20FD               |                | JRNZ-1H            |                                                                         |
| 0D2A            | 08                 |                | EX AF,AF'          |                                                                         |
| 0D2B            | 3D                 |                | DEC A              |                                                                         |
| 0D2C            | 20F7               |                | JRNZ-7H            | } Jump to WRITE unless end of line.                                     |
| 0D2E            | 10EA               |                | DJNZ-14H           |                                                                         |
| 0D30            | 19                 |                | ADD HL,DE          | Move to next line.                                                      |
| 0D31            | 7C                 |                | LD A,H.            | } Detect end of table.                                                  |
| 0D32            | FE 0A              |                | CP 0AH.            |                                                                         |
| 0D34            | 20 E2              |                | JRNZ - 1CH         | Jump to LINE unless table ended.                                        |
| 0D36            | 0E 20              |                | LD C, 20H          | Set space code for next pass.                                           |
| 0D38            | C9                 |                | RET                | Return to calling routine above.                                        |

Rather than giving a full description of this programme, it is left to those who wish to analyse or modify it to learn from so doing. Note that a different register has been chosen to store the character code so as to leave the accumulator free. There is nothing ideal about the methods used in this (or any other programme). The essential criterion is simply "DOES IT PERFORM THE ALLOTTED TASK AND NOT HAVE ANY HARMFUL SIDE EFFECTS?" (such as overwriting a section of memory reserved for another purpose by the programmer).

SECTION F: PROGRAMMING HINTS

You should soon be able to write any programme your time, growing skill, peripherals and RAM capacity will allow (be it a computer game, a personal diary, a business accounting system or just a moving 'video wallpaper' pattern). Of course the longer programmes are much easier and quicker to write with the aid of an Assembler or High Level Language facilities but in the interim here are some essentials and ideas to enable you to use your NASCOM 1 to the full. More information may be gleaned by studying the various magazines and the NASBUG listing.

Some NASBUG Subroutines, Etc. (See also page 47)

1. CD 6900 = CALL 0069H (CALL KBD). This scans the keyboard and if a key is pressed returns the corresponding Hex code in A and sets the carry flag.
2. CD 3B 01 =CALL 013BH (CALL CRT)This takes a code previously placed in A and displays the character corresponding to the 7 least significant bits in the present cursor position on the screen (and moves the cursor on). If the code in A was 1EH then the screen will be cleared.
3. CD 3C 02 = CALL 023CH (CALL SPACE). Moves cursor on one position.
4. CD 40 02 = CALL 0240H (CALL CRLF). Scrolls display up one line.
5. CD 44 02 = CALL 0244 H (CALL B2 HEX). Takes 8 bit byte in A and displays the two digit hexadecimal representation of it on screen.
6. CD 35 00 = CALL 0035H (CALL KDEL). Returns after 7½ ms delay (and clears A).
7. C3 86 02 = JP 0286H (JP PARSE). Jump into main monitor loop scanning UART and keyboard for data/commands.
8. To re-write CRT (Screen display) routine or amend it:- insert address of new routine in 0C4B and 4CH.
9. Ditto, for keyboard scanning routine: 0C4E and 4FH.
10. To redefine Command table insert starting address of new table at 0C45 and 46H.
11. Ditto, for keyboard table: 0C43 and 44H.
12. Insert length of new keyboard table in 0C3F and 40H.
13. Insert origin (if different) of new keyboard table in 0C41 and 42. (In each case the most significant byte is placed last).
14. The Command table may be disabled by typing:-  
MC45<sub>NL</sub> then FF•NL

15. The spare output bits from port zero can be controlled by setting or resetting the corresponding bits in location 0C00H while the monitor remains in use.
16. The first address available for user programming is 0C50H (Not 0C60H as indicated elsewhere).

#### Z80 Programming Hints

17. To clear the accumulator you may use either:-

```
3E 00 LD A, 00H.
or: AF XOR A.
```

The only advantage of the former is that it does not affect the flags.

18. If you require to set flags (e.g. after loading A) then you may use:-

```
B7 OR A
```

without changing the contents of A.

19. If an arbitrary no. in the range 00H to 7FH would be useful try:-

```
ED 5F LD A, R.
```

Although this is a random number the first time it is used, it will be predictably different a fixed number of M1 states later.

20. To copy the carry flag to all bits in A use:-

```
9F SBC A, A.
```

21. To copy the carry flag to all bits in H and L use:-

```
ED 62 SBC HL, HL.
```

22. To initialise PIO ports as outputs from the NASCOM 1 use:-

```
3E 0F LD A, 0FH (0F = 'MODE 0')
D3 06 OUT (06), A. (for port 4).
D3 07 OUT (07), A (for port 5).
```

23. To initialise PIO ports as inputs to the NASCOM 1 you may use:-

```
3E 4F LD A, 4FH (4F = 'MODE 1')
D3 06 OUT (06),A (for port 4).
D3 07 OUT (07),A (for port 5).
```

(For details see PIO Handbook).

24. To assist in the calculation of relative jumps here is a brief table:-

| <u>Jump (Decimal)</u> | <u>Jump (HEX)</u> | <u>Object Code (2nd Byte)</u> |
|-----------------------|-------------------|-------------------------------|
| -126 (max.)           | -7EH              | 80                            |
| - 62                  | -3EH              | C0                            |
| - 32                  | -20H              | DE                            |
| - 30                  | -1EH              | E0                            |
| - 16                  | -10H              | EE                            |
| - 14                  | -0EH              | F0                            |
| - 12                  | -0CH              | F2                            |
| - 10                  | -0AH              | F4                            |
| - 9                   | -09H              | F5                            |
| - 8                   | -08H              | F6                            |
| - 7                   | -07H              | F7                            |
| - 6                   | -06H              | F8                            |
| - 5                   | -05H              | F9                            |
| - 4                   | -04H              | FA                            |
| - 3                   | -03H              | FB                            |
| - 2                   | -02H              | FC                            |
| - 1                   | -01H              | FD                            |
| + 3                   | +03H              | 01                            |
| + 4                   | +04H              | 02                            |
| + 5                   | +05H              | 03                            |
| + 6                   | +06H              | 04                            |
| + 7                   | +07H              | 05                            |
| + 8                   | +08H              | 06                            |
| + 16                  | +10H              | 0E                            |
| + 18                  | +12H              | 10                            |
| + 32                  | +20H              | 1E                            |
| + 64                  | +40H              | 3E                            |
| +128                  | +80H              | 7E                            |
| +129 (max).           | +81H              | 7F                            |

SECTION 6: Conversion Between 8080 and Z80 Programmes

The Z80 machine code instruction set is an expanded version (or superset) of that for the earlier 8080 microprocessor. It includes 2 byte opcodes and 4 byte instructions (max. 3 for the 8080). An 8080 machine code programme will therefore run on the Z80 but not vice-versa unless any specific Z80 codes used are re-written in a longer form. The additional Z80 instructions (e.g. to use relative jumps or the index registers) all begin with:-

08, 10, 18, 20, 28, 30, 38, CB, D9, DD, ED or FD.

(Note that 20 and 30 are used by the 8085 for special instructions - read/set interrupt mask - not compatible with the Z80).

The mnemonics specified in the two microprocessors' assembly languages are however very different and so the NASCOM 1 user who wishes to use and understand any of the many published 8080 programme listings may find the following conversion table useful:

MNEMONIC CONVERSION TABLE

| 8080 |     | Z80  |          | 8080 |      | Z80  |           |
|------|-----|------|----------|------|------|------|-----------|
|      |     |      |          | DCR  | r    | DEC  | r         |
|      |     |      |          | DCR  | M    | DEC  | (HL).     |
|      |     |      |          | DCX  | B    | DEC  | BC        |
|      |     |      |          | DCX  | D    | DEC  | DE        |
|      |     |      |          | DCX  | H    | DEC  | HL        |
|      |     |      |          | DCX  | SP   | DEC  | SP        |
|      |     |      |          | DI   |      | DI   |           |
|      |     |      |          | EI   |      | EI   |           |
|      |     |      |          | HLT  |      | HALT |           |
|      |     |      |          | IN   | n    | IN   | A, (n)    |
|      |     |      |          | INR  | r    | INC  | r         |
|      |     |      |          | INR  | M    | INC  | (HL)      |
|      |     |      |          | INX  | B    | INC  | BC        |
|      |     |      |          | INX  | D    | INC  | DE        |
|      |     |      |          | INX  | H    | INC  | HL        |
|      |     |      |          | INX  | SP   | INC  | SP        |
|      |     |      |          | JC   | nn   | JP   | C,nn      |
|      |     |      |          | JM   | nn   | JP   | M,nn      |
|      |     |      |          | JMP  | nn   | JP   | nn        |
|      |     |      |          | JNC  | nn   | JP   | NC,nn     |
|      |     |      |          | JNZ  | nn   | JP   | NZ,nn     |
|      |     |      |          | JP   | nn   | JP   | P,nn      |
|      |     |      |          | JPE  | nn   | JP   | PE,nn     |
|      |     |      |          | JPO  | nn   | JP   | PO,nn     |
|      |     |      |          | JZ   | nn   | JP   | Z,nn.     |
|      |     |      |          | LDA  | nn   | LD   | A, (nn).  |
|      |     |      |          | LDAX | B    | LD   | A, (BC).  |
|      |     |      |          | LDAX | D    | LD   | A, (DE).  |
|      |     |      |          | LHLD | nn   | LD   | HL, (nn). |
|      |     |      |          | LXI  | B,nn | LD   | BC,nn.    |
| 8080 | Z80 |      |          |      |      |      |           |
| ACI  | n   | ADC  | A,n.     |      |      |      |           |
| ADC  | r   | ADC  | A,r.     |      |      |      |           |
| ADC  | M   | ADC  | A, (HL). |      |      |      |           |
| ADD  | r   | ADD  | A,r      |      |      |      |           |
| ADD  | M   | ADD  | A, (HL). |      |      |      |           |
| ADI  | n   | ADD  | A,n.     |      |      |      |           |
| ANA  | r   | AND  | r        |      |      |      |           |
| ANA  | M   | AND  | (HL)     |      |      |      |           |
| ANI  | n   | AND  | n        |      |      |      |           |
| CALL | nn  | CALL | nn       |      |      |      |           |
| CC   | nn  | CALL | C,nn.    |      |      |      |           |
| CM   | nn  | CALL | M,nn.    |      |      |      |           |
| CMA  |     | CPL  |          |      |      |      |           |
| CMC  |     | CCF  |          |      |      |      |           |
| CMP  | r   | CP   | r        |      |      |      |           |
| CMP  | M   | CP   | (HL)     |      |      |      |           |
| CNC  | nn  | CALL | NC, nn   |      |      |      |           |
| CNZ  | nn  | CALL | NZ,nn    |      |      |      |           |
| CP   | nn  | CALL | P,nn.    |      |      |      |           |
| CPI  | n   | CP   | n        |      |      |      |           |
| CPE  | nn  | CALL | PE,nn    |      |      |      |           |
| CPO  | nn  | CALL | PO,nn    |      |      |      |           |
| CZ   | nn  | CALL | Z,nn     |      |      |      |           |
| DAA  |     | DAA  |          |      |      |      |           |
| DAD  | B   | ADD  | HL,BC.   |      |      |      |           |
| DAD  | D   | ADD  | HL,DE.   |      |      |      |           |
| DAD  | H   | ADD  | HL,HL.   |      |      |      |           |
| DAD  | SP  | ADD  | HL,SP    |      |      |      |           |

| 8080 |        | Z80  |          | 8080 |        | Z80  |          |
|------|--------|------|----------|------|--------|------|----------|
| LXI  | D,nn   | LD   | DE,nn.   | RP   |        | RET  | P        |
| LXI  | H,nn   | LD   | HL,nn.   | RPE  |        | RET  | PE       |
| LXI  | SP,nn  | LD   | SP,nn.   | RPO  |        | RET  | PO       |
| MOV  | r,r'   | LD   | r,r'     | RRC  |        | RRCA |          |
| MOV  | M,r    | LD   | (HL), r. | RST  | 0      | RST  | 00H      |
| MOV  | r,M    | LD   | r, (HL)  | RST  | 1      | RST  | 08H      |
| MVI  | r,n    | LD   | r,n      | RST  | 2      | RST  | 10H      |
| MVI  | M,n    | LD   | (HL),n   | RST  | 3      | RST  | 18H      |
| NOP  |        | NOP  |          | RST  | 4      | RST  | 20H      |
| ORA  | r      | OR   | r        | RST  | 5      | RST  | 28H      |
| ORA  | M      | OR   | (HL)     | RST  | 6      | RST  | 30H      |
| ORI  | n      | OR   | n        | RST  | 7      | RST  | 38H      |
| OUT  | n      | OUT  | (n),A    | RZ   |        | RET  | Z        |
| PCHL |        | JP   | (HL)     | SBB  | r      | SBC  | A,r      |
| POP  | B      | POP  | BC       | SBB  | M      | SBC  | A,(HL)   |
| POP  | D      | POP  | DE       | SBI  | n      | SBC  | A,n      |
| POP  | H      | POP  | HL       | SHLD | nn     | LD   | (nn),HL. |
| POP  | PSW    | POP  | AF       | SIM  | (8085) | -    |          |
| PUSH | B      | PUSH | BC       | SPHL |        | LD   | SP,HL.   |
| PUSH | D      | PUSH | DE       | STA  | nn     | LD   | (nn),A.  |
| PUSH | H      | PUSH | HL       | STAX | B      | LD   | (BC), A. |
| PUSH | PSW    | PUSH | AF       | STAX | D      | LD   | (DE),A.  |
| RAL  |        | RLA  |          | STC  |        | SCF  |          |
| RAR  |        | RRA  |          | SUB  | r      | SUB  | r        |
| RC   |        | RET  | C        | SUB  | M      | SUB  | (HL)     |
| RET  |        | RET  |          | SUI  | n      | SUB  | n        |
| RIM  | (8085) | -    |          | XCHG |        | EX   | DE,HL    |
| RLC  |        | RLCA |          | XRA  | r      | XOR  | r        |
| RM   |        | RET  | M        | XRA  | M      | XOR  | (HL)     |
| RNC  |        | RET  | NC       | XRI  | n      | XOR  | n        |
| RNZ  |        | RET  | NZ       | XTHL |        | EX   | (SP),HL. |

KEY

r or r' = Register A, B, C, D, E, H or L  
n = 8 bit number or port address.  
nn = 16 bit number or memory address.

Note in particular the following possible sources of confusion:-

| <u>8080</u> | <u>Z80</u> |
|-------------|------------|
| CP          | = CALL P   |
| CMP or CPI  | = CP       |
| -           | = CPI      |
| JP          | = JP P     |
| JMP         | = JP       |

In order to keep 8080 compatibility together with an expanded instruction set a few different Z80 opcodes happen to have the same functional effect.

e.g. (one byte): 0F RRCA  
=(two byte): CB 0F RRC A

SECTION H: LAST WORD

Please keep in touch with us via the NASCOM USERS CLUB, and let us know your problems and successes. We also welcome lists of any corrections or suggested additions to our or the relevant manufacturers' data in order to keep everyone equally informed (via the club newsletter).

We look forward to sharing with you a continuing role in the microprocessor revolution.